# Taneytown, MD

Phone: +14107562430
115 York St
Taneytown, Maryland
Email: adam@hitchman.com

---



## Toro 60" ZMaster 2000 Commercial Zero Turn Lawn Mower(77292), 23.5 HP Kawasaki FX & VooDoo Tires

| | | | |
|---|---|---|---|
| **Type** | Equipment | **Category** | Lawn Mowers |
| **Stock#** | T77292 | **Location** | Taneytown, MD |
| **Year** | 2026 | **Status** | Special Order |
| **Condition** | New | **Manufacturer** | Toro |
| **Model** | 2000 Series MyRIDE HDX 60" (152 cm) 23.5 HP 726cc (77294) | **Floor Width** | 60in / 5ft |
| **Color** | Red | | |

https://thehitchmaninc.com/unit/toro-60-zmaster-2000-commercial-zero-turn-lawn-mower-77292-23-5-hp-kawasaki-fx-voodoo-tires-1078256

**Call for Price**

---

**Description**

***Price listed is Toro Suggested Promo Pricing. Please call us to discuss available pricing discounts, Fleet pricing, etc.

- TURBO FORCE® Cutting Deck - Built to last. Enjoy years of reliable performance with an upgraded 7-gauge steel, 5.5" deep deck.
- Low-Back Suspension Seat - Stay comfortable on the job with the premium low-back shock absorbing suspension seat.
- 24" Voodoo Trac™ Drive Tires - Get the ultimate in aggressive tread and styling with 24" Voodoo Trac™ Drive Tires.

**Specifications**
Anti Scalp Wheels Standard
Blade Tip Speed 18,500 ft/min / 5,638 m/min
Caster Tires 13 in. x 6.5 in. - 6 in. (33 cm x 16.5 cm - 15.2 cm) Pneumatic
Clutch Electromagnetic
Deck Design 5.5” (14 cm) deck depth, 7-Gauge High-Strength Steel TURBO FORCE® w/ bull-nose bumper
Deck Size 60 in / 152 cm
Discharge Chute Rubber
Drive Tires Voodoo Trac 24 in. x 9.5 in. - 12 in. (61 x 24.1 - 30.5 cm)
Engine 23.5 hp* Kawasaki® FX730V 726 cc
Engine Brand Kawasaki
Engine Displacement (cc) 726 cc
Engine Horsepower 23.5 hp
Foot Operated Height of Cut Standard
Forward Ground/Transport Speed Up to 10.0 mph / 16.0 kph
Fuel Capacity 7 gal. / 26.5 L / 28 Qt.
Fuel Type Gasoline
Height of Cut 1.5 - 5.0 in. / 3.8 - 12.7 cm in 0.25 in (0.64 cm) increments
Hitch Bracket Standard
Hour Meter Standard
Ignition Electric
Lighting LED Headlights
Notes Hitch: Integrated Receiver Hitch - 2 in. x 2 in. 80 lbs. (36.3 kg) max tongue, 250 lbs. (113.4 kg) max tow
Product Type Zero Turn Mowers
Product Use Commercial
Roll-Over Protection System (ROPS) Folding; Standard
Seat Deluxe Suspension Seat
Spindle Housing 8 in / 20.3 cm Diameter Aluminum (Non Greasable) Ball Bearing, 1 in / 2.5 cm Shaft
Start Type Electric
Steering Controls 1.4" (3.6 cm) Diameter Grips; Adjustable, Dampened
Tool Mounting Capability Side Console / Rear Guard Ready
Transmission Hydro-Gear ZT-3400
Weight 1,014 lbs / 459.9 kg