

Roxbury Trailers

ROXBURY
TRAILERS

Phone: +19732242171
364 West Dewey Ave
Wharton, New Jersey
Email: sales@roxburytrailers.com



2026 Sure-Trac 8.5x20+4 15K SD Beavertail Deckover Trailer

Type	Trailer or Truck Bed	Category	Deckover Trailer
Stock#	9033	Location	Roxbury Trailers
Year	2026	Status	On Order
Condition	New	Manufacturer	Sure-Trac
Model	8.5x20+4 15K SD Beavertail Deckover Equipment Trailer	Floor Length	240in / 20ft
Floor Width	102in / 8ft 6in	Floor Height	36in / 3ft
GVWR	15000	Weight	3475
Payload Capacity	11525	Axle Capacity	7000
Color	Black	Wheels	16", 8-Lug Steel
Coupler	Adjustable	Jack	12K Drop Leg, Set-Back
Pull Type	Bumper	Axles	2
Suspension Type	Leaf Spring Suspension	Msrp	10593

Construction	Steel	Warranty	3-Year Frame and Component Overall Protection 1-Year Tire Hazard and Abuse Protection 5-Year Standard Tire Warranty 5-Year Axle and Suspension Warranty
Length	366in / 30ft 6in	Brakes	YES - Electric/ Both Axles
Lights	LED	Tires	ST235/80R16E 10-PLY
Load Securement	(6) 1/2" D-Rings, Stake Pockets and Rub Rail	Beavertail	4ft
Frame	10", 12 lb/ft I-Beam, Side Rails - 5" Steel Channel		

<https://roxburytrailers.com/unit/2026-sure-trac-8-5x20-4-15k-sd-beavertail-deckover-trailer-1161486>

Price: \$9,995.00

MSRP: \$10,593.00

Description

2026 Sure-Trac 8.5x24 (20+4) SD Beavertail Deckover Trailer 15K

Full-Width Material and Equipment Transport Platform

The 2026 Sure-Trac Standard Duty (SD) Beavertail Deckover is engineered for operations requiring a completely flat, full-width loading deck unobstructed by interior wheel wells. This 15,000 lb. GVWR platform is designed specifically for commercial contractors, agricultural operations, and landscape crews who need to haul wide-track machinery, side-load standard building pallets, or transport long material bundles.

Built on a heavy-duty 10-inch structural steel I-beam chassis, this trailer provides a true 102-inch deck width. By utilizing a 20-foot flat deck paired with a 4-foot sloping beavertail and 5-foot spring-assisted stand-up ramps, it delivers a practical loading configuration for intermediate and heavy-duty commercial payloads.

Target Applications: Who This Trailer Is For

- Commercial Material Supply: Side-loading multiple pallets of roofing, masonry supplies, or lumber utilizing a forklift with complete deck clearance.
- Medium-Duty Excavation & Trenching: Moving mid-sized skid steers, track loaders, or attachments that require a broad platform and high ground clearance.

- Agricultural & Turf Fleets: Transporting wide tractors, commercial hay bales, or dual-wheel turf machinery that exceeds standard 82-inch between-fender profiles.

Key Capacities & Dimensions

- GVWR: 15,000 lbs
 - Curb Weight: 3,475 lbs
 - Net Payload Capacity: 11,525 lbs
 - Deck Dimensions: 8.5' Wide (102") x 24' Total Length (20' Flat Deck + 4' Beavertail)
 - Deck Height: 36" Low-Profile Deckover Clearance
 - Overall Length: 366"
-

Technical Specifications

Main Frame 10" at 12 lb/ft Structural Steel I-Beam
Tongue & Hitch 10" Flange, 12 lb/ft I-Beam / 2-5/16" Adjustable Coupler
Side Rails 5" Steel Channel Perimeter Layout
Crossmembers 3" Steel Channel on 16" On-Center Spacing
Running Gear (2) 7,000 lb. Slipper Spring Brake Axles
Tires & Wheels ST235/80R16E 10-PLY Radial Tires on 16" 8-Lug Steel Wheels
Decking 2" Pressure-Treated Pine Wood Flooring
Rear Ramps 5' Tall Spring-Assist Stand-Up Ramps with Adjustable Support Legs
Front Bulkhead Heavy-Duty Tubular Steel Safety Bulkhead
Tie-Down Infrastructure (6) 1/2" Recessed D-Rings, Stake Pockets, and Continuous Rub Rail
Storage Provisions Ready for Drop-In (Recessed) Lockable Toolbox / Spare Tire Carrier
Electrical / Lighting Full DOT Compliant LED Lighting / Round 7-Pin Blade Plug

Structural Design & Fleet Highlights

1. 10" Structural I-Beam & 16" On-Center Framing

The core foundation utilizes a heavy 10-inch at 12 lb/ft structural steel I-beam frame and matching wrapped tongue to eliminate center-bowing under load. To prevent floor sagging from concentrated wheel weight, the frame is interconnected with 3" steel channel crossmembers spaced at 16 inches on-center, supported by a robust 5" channel side rail perimeter.

2. Unobstructed 102" Flat Deck Clearance

By raising the deck to a 36-inch height directly above the running gear, this trailer completely deletes interior wheel arches. Forklifts can pull straight up to the side rails to load pallets cleanly, and wide-track equipment can utilize the entire width of the trailer without risk of damaging tire sidewalls on steel fenders.

3. 4' Beavertail with 5' Spring-Assist Stand-Up Ramps

Loading wheeled machinery onto a 36-inch deck requires a stable approach configuration. This model combines a 4-foot sloping beavertail with heavy-duty 5-foot stand-up ramps. The ramps feature an integrated spring-assist mechanism to minimize lifting effort and are built with adjustable rear support legs that brace against the ground during loading, preventing the trailer tongue from lifting your tow vehicle.

4. Heavy Cargo Security & Infrastructure Protection

- **Rub Rail & Stake Pockets:** A heavy-duty steel rub rail and integrated stake pockets run the entire length of both side frames, providing limitless tie-down positions for commercial ratchet straps and chain binders.
- **Heavy-Duty Tube Bulkhead:** The front features a rigid, fully welded tubular steel bulkhead that serves as a permanent forward load-stop to shield the tow vehicle from shifting cargo.
- **Recessed Storage Integration:** The tongue structure comes pre-configured to accept a factory drop-in, recessed lockable steel toolbox, keeping chains, binders, and tools secured and out of the elements.

5. Commercial Slipper Spring Axles & 10-Ply Tires

Designed for stable highway tracking under load, this unit rides on dual 7,000 lb. heavy-duty slipper spring axles with electric brakes on all hubs. Power is delivered to the asphalt through full commercial-grade 10-ply radial tires (ST235/80R16E) mounted on heavy 8-lug steel wheels, providing a highly reliable tracking network for heavy long-distance hauls.

Pricing & Yard Terms

- **Price:** Cash/Check Price
 - **Processing Fees:** A 3% processing fee applies to credit card transactions.
 - **Dealer Fees:** \$0. We charge absolutely zero documentation, prep, or administrative fees.
 - **Documentation:** Temporary license plate/transit registration included with all trailer purchases.
 - **Sales Tax:** NJ residents pay 6.625% sales tax at purchase. Out-of-state buyers pay applicable sales tax when registering the unit in their home state.
 - **Availability:** Please call the shop directly to verify current lot inventory.
-