Acton

Phone: +16612331166
4519 Sierra Highway
Acton, California
Email: nsultana@tss786.com



2025 Mahindra 1126 TL Tractor

Type	Equipment	**Category**	Tractor
Stock#	18167	**VIN**	MBNMCMYADRZG00983
Location	Acton	**Year**	2025
Status	Available	**Condition**	New
Manufacturer	Mahindra	**Model**	1126 TL
Msrp	27499.99	**Monthly Payment**	467

https://tss786.com/unit/2025-mahindra-1126-tl-tractor-1233212

Price: $24,983.00

MSRP: $27,499.99
Monthly Payment: $467.00

Description

Condition: New
Manufacturer: Mahindra
Model: 1126 HST
Series: 1100 Series
Tractor Type: Sub-Compact Utility Tractor
Engine Power: 25.3 HP

Engine: Mitsubishi MLV3E3 3-Cylinder Diesel
Engine Displacement: 67.2 cu. in. / 1,102 cc
Rated Engine Speed: 3,000 RPM
Drive: 4WD
Transmission: 2-Range Hydrostatic (HST)
Fuel Capacity: 6.6 Gallons
Steering: Hydrostatic Power Steering
Engine
Mitsubishi MLV3E3 Four-Stroke, Naturally Aspirated, Indirect-Injection, Water-Cooled Diesel Engine
Horsepower
25.3 HP (18.9 kW) @ 3,000 RPM
Displacement
67.2 cu. in. (1,102 cc)
Cylinders
3-Cylinder Diesel
Fuel Capacity
6.6 Gallons
Emission System
No DPF – No Diesel Particulate Filter Regeneration Required
Drive System
Four-Wheel Drive (4WD)
Transmission
2-Range Hydrostatic Transmission (HST)
Travel Speeds
Infinite Forward and Reverse
Brakes
Single-Pedal Brake System
Steering
Hydrostatic Power Steering
Rear PTO
Live Rear PTO
Rear PTO Speed
540 RPM @ 2,837 Engine RPM
Mid PTO
2,500 RPM @ 2,837 Engine RPM
PTO Horsepower
19.5 HP
Hydraulic System
Open-Center, Full-Live Hydraulic System with Position Control
Hydraulic Pump Output
11.2 GPM
3-Point Hitch
Category I Three-Point Hitch with Check Chains
3-Point Hitch Lift Capacity
770 lbs
Rear Auxiliary Remote Valves
Available Rear Hydraulic Remote Valves
Compatible Front-End Loader
Mahindra L11 Front Loader

Loader Lift Capacity
794 lbs at Full Height at Pivot Pin
Loader Maximum Lift Height
68"
Loader Breakout Force
1,433 lbs
Loader Digging Depth
3"
Loader Bucket Width
50"
Loader Bucket Capacity – Heaped
6.5 cu. ft.
Loader Bucket Capacity – Struck
5.05 cu. ft.
Loader Weight
Approx. 406 lbs
Wheelbase
55.1"
Overall Length
100.4"
Overall Width
46.3"
Overall Height – Open Station
86.6"
Minimum Ground Clearance
6.7"
Turning Radius
7.2'
Tractor Weight – Open Station
Approx. 1,620 lbs
Industrial Tires
Front: 18 x 8.5-10
Rear: 26 x 12-12
Turf Tires
Front: 18 x 8.5-10
Rear: 26 x 12-12
Battery
12.6V, 650 CCA
Alternator
12V, 55 Amp
Operator Features
mComfort Seat, Hydrostatic Power Steering, Ergonomically Positioned Controls, Easy-to-Read Instrumentation, Projector-Style Headlights and Convenient Operator Platform
Technology
Mahindra myOJA Connectivity
Warranty
7-Year Limited Powertrain Warranty
Overall Construction
Powerful and versatile 25.3 HP sub-compact utility tractor designed to deliver maximum performance from Mahindra's 1100 Series platform. The 1126 HST features four-wheel drive, a 2-

range hydrostatic transmission, hydrostatic power steering, rear and mid PTOs, Category I three-point hitch, and compatibility with the Mahindra L11 front-end loader. When equipped with the L11 loader, it delivers 794 lbs of lift capacity at full height and 1,433 lbs of breakout force. Its compact dimensions, tight 7.2' turning radius, and powerful 25.3 HP diesel engine make it ideal for property maintenance, material handling, mowing, landscaping, grading, snow removal, ranch work, and general-purpose tractor applications.