Acton

Phone: +16612331166
4519 Sierra Highway
Acton, California
Email: nsultana@tss786.com

2026 Mahindra 2126 TL Tractor

Type	Equipment	**Category**	Tractor
Stock#	18415	**VIN**	MBNMFL6DKSZJ02862
Location	Acton	**Year**	2026
Status	Available	**Condition**	New
Manufacturer	Mahindra	**Model**	2126 TL
Msrp	39399.99	**Monthly Payment**	610

https://tss786.com/unit/2026-mahindra-2126-tl-tractor-1233332

Price: $37,599.99

MSRP: $39,399.99
Monthly Payment: $610.00

Description

Condition: New
Manufacturer: Mahindra
Model: 2126 HST
Series: 2100 Series
Tractor Type: Compact Utility Tractor
Configuration: Tractor + Front-End Loader

Engine Power: 25.3 HP
Engine: Mitsubishi MVS3L2 3-Cylinder Diesel
Engine Displacement: 80.4 cu. in. / 1,318 cc
Rated Engine Speed: 2,700 RPM
Drive: 4WD
Transmission: 3-Range Hydrostatic (HST)
Fuel Capacity: 5.8 Gallons
Steering: Hydrostatic Power Steering
Engine
Mitsubishi MVS3L2 Four-Stroke, Naturally Aspirated, Indirect-Injection, Water-Cooled Diesel Engine
Horsepower
25.3 HP (18.9 kW) @ 2,700 RPM
Displacement
80.4 cu. in. (1,318 cc)
Cylinders
3-Cylinder Diesel
Compression Ratio
22:1
Fuel Capacity
5.8 Gallons
Emission System
No DPF – No Diesel Particulate Filter Regeneration Required
Drive System
Four-Wheel Drive (4WD)
Transmission
3-Range Hydrostatic Transmission (HST)
Travel Speeds
Infinite Forward and Reverse
Maximum Travel Speed
11.2 MPH
Brakes
Two-Pedal Brake System
Steering
Hydrostatic Power Steering
Rear PTO
Live Rear PTO
Rear PTO Speed
540 RPM @ 2,376 Engine RPM
Mid PTO
2,500 RPM @ 2,500 Engine RPM
PTO Horsepower
18.8 HP
Hydraulic System
Open-Center, Full-Live Hydraulic System with Position Control
Maximum Hydraulic Flow
11.2 GPM
Main Hydraulic Pump
6.3 GPM
Steering Pump

5.0 GPM
3-Point Hitch
Category I Three-Point Hitch with Telescoping Stabilizers
3-Point Hitch Lift Capacity
1,760 lbs @ 24" Behind Lift Point
Rear Auxiliary Remote Valves
Optional Single or Dual Rear Hydraulic Remote Valves
Front-End Loader
Mahindra L21 Front Loader
Loader Lift Capacity
1,477 lbs at Full Height
Loader Maximum Lift Height
77"
Loader Digging Depth
3"
Loader Control
Single-Lever Joystick Loader Control
Wheelbase
61.4"
Overall Length
112.7"
Overall Width
54.4"
Overall Height – Open Station
93.6"
Minimum Ground Clearance
13.4"
Turning Radius
8.2'
Tractor Weight – Open Station
Approx. 2,101 lbs
Industrial Tires
Front: 8.5 x 14
Rear: 12.4-16
Turf Tires
Front: 8.5 x 14
Rear: 13.5-16
Battery
12V, 650 CCA
Alternator
12V, 55 Amp
Operator Features
mComfort Operator Seat with Foldable Armrests, Hydrostatic Power Steering, 3-Range HST, Electronic PTO Engagement, Ergonomically Positioned Controls, Smooth Loader Joystick and Spacious Operator Platform
Technology
Mahindra myOJA Connected Tractor Technology
Warranty
7-Year Limited Powertrain Warranty
Overall Construction

Powerful and versatile 25.3 HP compact utility tractor designed to combine a maneuverable footprint with impressive lifting and implement capability. The Mahindra 2126 HST features four-wheel drive, a smooth 3-range hydrostatic transmission, hydrostatic power steering, live rear PTO, mid PTO, Category I three-point hitch, and Mahindra's L21 front-end loader. The L21 delivers up to 1,477 lbs of loader lift capacity at full height, while the three-point hitch provides 1,760 lbs of lift capacity at 24" behind the lift point. With 13.4" of ground clearance and a tight 8.2' turning radius, the 2126 is ideal for material handling, landscaping, grading, mowing, ranch work, property maintenance, dirt work, and general-purpose tractor applications.