Newbury

Phone: +14405641234
14555 Ravenna Rd
Newbury, Ohio
Email: paul@oreillyequipment.com



2024 Cross Trailers 820TA-ALPHA Cargo / Enclosed Trailer 10k -7' Interior

Type	Trailer or Truck Bed	**Category**	Cargo / Enclosed Trailer
Stock#	014812	**VIN**	58E1W2025R1014812
Location	Newbury	**Year**	2024
Status	Available	**Condition**	Used
Manufacturer	Cross Trailers	**Model**	820TA-ALPHA
Floor Length	240in / 20ft	**Floor Width**	96in / 8ft
GVWR	9990	**Weight**	3489
Payload Capacity	6501		

https://oreillyequipment.com/unit/2024-cross-trailers-820ta-alpha-cargo-enclosed-trailer-10k-7-interior-1270011

Price: $9,000.00

Description

CROSS TRAILERS - ALPHA MODEL
STANDARD FEATURES:

- Structural Framing & BodyMain Frame: 2" x 6" welded tubular steel main frame.
- Tube Wall & Ceiling Studs: Fully integrated 16" on-center tube frame walls and roof studs for enhanced rigidity.
- Aegis System: Electrolysis and corrosion-resistant body design to minimize rust and extend trailer life.
- Flat Top Design: Reinforced flat roof structural engineering.
- Wedge Front: Arrow wedge or V-nose layout to improve fuel aerodynamics.

EXTERIOR FEATURES:

- Aluminum Skin: Durable .030 exterior aluminum sheets utilizing a screwless bonding system.
- One-Piece Roof: Seamless one-piece aluminum roof to safeguard against environmental leaks.
- Gravel Guard: 24" Aluminum Tread Plate (ATP) rock guard on the front profile.Hardware:
- Clear-coated, corrosion-resistant exterior door hardware.

INTERIOR FEATURES:

- Flooring: 3/4" water-resistant decking engineered to prevent moisture rot.
- Sidewalls: 3/8" water-resistant interior plywood walls.
- Standard Dimensions: Base configuration provides a 78" (6'6") interior wall height.Side
- Entry: 36" wide side RV door featuring an integrated stepwell.
- Rear Access: Heavy-duty rear ramp door built with multi-hinge reinforcement

SUSPENTION & TOWING:

- Axles: Dual 5,200 lb. spring tandem axles equipped with 4-way electric brakes and a safety breakaway kit.
- Tires: ST225/75R15 load range E radial tires mounted to 6-lug heavy-duty wheels.
- Hitch Coupler: 2 5/16" ball coupler mounted on a heavy steel A-frame.
- Jack: 5,000 lb. top-crank A-frame tongue jack

ELECTRICAL & CARGO MANAGEMENT:

- Tie-Downs: Four recessed 5,000 lb. rated steel D-rings welded to the framing.
- Exterior Lighting: Full exterior DOT-approved, high-efficiency white-out LED lighting.
- Interior Lighting: 12-volt LED high-lumen dome lights wired directly to a convenient interior wall switch.Connector: Standard 7-pin round electrical plug

---