

Double D Outdoor Equipment

Phone: +18505263456

4909 HWY 90

Marianna, Florida

Email: dylan@doubledoutdoor.com



2026 TYM Tractors T574H HST 4WD

Type	Equipment	Category	Tractor
Stock#	T574H	Location	Double D Outdoor Equipment
Year	2026	Status	Available
Condition	New	Manufacturer	TYM Tractors
Model	T574H HST 4WD		
Clearance Price	34999	Msrp	40560

<https://doubledoutdoor.com/unit/2026-tym-tractors-t574h-hst-4wd-1274544>

Price: \$34,999.00

MSRP: \$40,560.00

Sales Price: \$34,999.00

Description

SERIOUS POWER. HEAVY-DUTY CAPABILITY. TYM VALUE.

The TYM T574H is built for landowners, farmers, ranchers, and property owners who need more tractor without stepping all the way into a large utility tractor. With a 55 HP turbocharged diesel engine, 4WD, hydrostatic transmission, 3-point hitch, independent PTO, and powerful TX57 front-end loader, the T574H is ready for serious work.

Whether you're mowing pastures, maintaining roads, moving dirt and gravel, handling livestock chores, clearing property, or working with heavy 3-point implements, the T574H gives you the horsepower, hydraulic performance, and lifting capacity to get the job done. The T574H combines a compact footprint with utility-tractor-level capability, making it particularly useful where maneuverability and power are both important.

TRACTOR TECHNICAL SPECIFICATIONS

Engine

Engine: TYM 4-cylinder turbocharged diesel

Model: TYM T2300T2

Gross Engine Power: 55 HP

Displacement: 139.5 cu. in. / 2,286 cc

Rated Engine Speed: 2,600 RPM

Cylinders: 4

Emission: Tier 4

Transmission & Drivetrain

Transmission: Hydrostatic

HST Ranges: 3-range HST

Drive: 4WD

Steering: Hydrostatic power steering

Brakes: Wet-disc

Independent PTO: Yes

Rear PTO: 540 RPM

3-Point Hitch

Hitch Category: Category I/II

Maximum Lift Capacity: 3,822 lb

Telescopic lower links

Telescopic stabilizers

Position and draft control

TYM's current published T574 specification lists the 3-point hitch lift capacity at 3,822 lb (1,733 kg).

Hydraulic System

Total Hydraulic Flow: Approximately 11.9 GPM

Implement Flow: Approximately 7.7 GPM

Steering Flow: Approximately 4.2–4.3 GPM

Open-center hydraulic system

Multiple rear hydraulic valve options

3rd-function installation available for compatible front attachments

The hydraulic system provides the flow necessary for loader operation and a wide range of hydraulic implements.

PTO

Rear PTO: 540 RPM

Independent PTO

Approximately 44 HP PTO output depending on configuration/specification.

Capacities

Fuel Tank: Approximately 17.0 gallons

Transmission/Hydraulic System: Approximately 9.2 gallons

Engine Oil: Approximately 6.8 qt

Coolant: Approximately 6.9 qt

Dimensions & Weight

Overall Length: 141.3"

Overall Width: 63.8"

Wheelbase: 76.2"

Ground Clearance: 13.8"

Height to Top of ROPS: Approximately 102.1"

Operating Weight with ROPS: Approximately 3,887 lb

Current TYM and dealer specifications list the T574 at approximately 141.3" long, 63.8" wide, with a 76.2" wheelbase and 13.8" minimum ground clearance.

TX57 FRONT-END LOADER

The TYM TX57 front-end loader turns the T574H into a serious material-handling machine. With a 2,790-lb lift capacity and 72-inch bucket, it has the muscle to handle dirt, gravel, mulch, manure, firewood, brush, and other materials around the farm or property.

Loader Specifications

Loader Model: TYM TX57

Maximum Lift Height to Pivot Pin: Approximately 109.4–110.2"

Maximum Lift Capacity: 2,790 lb

Bucket Width: 72"

Bucket Capacity: Approximately 11.3 cu. ft.

Maximum Lift Height Under Level Bucket: Approximately 101"

Clearance with Bucket Dumped: Approximately 83.6–84.4"

Reach at Maximum Lift Height: Approximately 17.6"

Reach with Bucket on Ground: Approximately 70.9–71.5"

Maximum Dump Angle: Approximately 45–50°

Maximum Rollback Angle: Approximately 35–40°

Digging Depth: Approximately 4.4–5.5"

Breakout Force at Ground Level: 5,316 lb

Bucket Rollback Force: 4,356 lb

Loader Relief Pressure: Approximately 2,489 PSI

Rated Loader Hydraulic Flow: Approximately 7.7 GPM
