

ZT3500



	ZT3500 - 48" Deck	ZT3500 - 52" Deck	ZT3500 - 61" Deck
DECK			
Cutting Height Range	1.5-4.8 in	1.5-4.8 in	1.5-4.8 in
Discharge Chute	Flexible molded polymer	Flexible molded polymer	Flexible molded polymer
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts
Mower Blade Tip Speed	17,365 ft/min	18,142 ft/min	18,809 ft/min
Width	48 in	52 in	61 in
ENGINE			
Fuel Tank	7.8 gal	7.8 gal	7.8 gal
Horsepower	20.5 hp	22 hp	23.5 hp
Engine Model	Kawasaki FX651V	Kawasaki FX691V	Kawasaki FX730V
WEIGHT			
Machine Weight	773 lbs	789 lbs	832 lbs
POWER/ELECTRICAL			
Clutch	125 ft-lb	125 ft-lb	125 ft-lb
Charging System	15 amp	15 amp	15 amp
TRANSMISSION			
Transmission Type	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
Oil Capacity	4 qt	4 qt	4 qt
Travel Speed	10 mph	10 mph	10 mph
Travel Speed - Reverse	3.5 mph	3.5 mph	3.5 mph
WHEELS			
Drive Wheel Size	23 x 10.5-12	23 x 10.5-12	23 x 10.5-12
Caster Arm Attachment	Welded to frame	Welded to frame	Welded to frame
Front Caster Wheel Size	13 x 6.5-6	13 x 6.5-6	13 x 6.5-6
FRAME			
Length	80 in	80 in	81.9 in
Front and Rear	Welded 7-gauge steel; 1.5 x 2.5 in steel tubing	Welded 7-gauge steel; 1.5 x 2.5 in steel tubing	Welded 7-gauge steel; 1.5 x 2.5 in steel tubing
SEAT			
Seat	High-back, mechanical suspension seat	High-back, mechanical suspension seat	High-back, mechanical suspension seat
Fore-Aft Adjustment	Seat slide lever	Seat slide lever	Seat slide lever