



	ZT3000 - 48" Deck	ZT3000 - 52" Deck	ZT3000 - 61" Deck
DECK			
Cutting Height Range	1.5-4.8 in	1.5-4.8 in	1.5-4.8 in
Discharge Chute	Flexible molded polymer	Flexible molded polymer	Flexible molded polymer
Mower Deck	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts	TufDeck™ Pro 10-gauge Top with 7-gauge Spindle Supports; 7-gauge Side Skirts
Mower Blade Tip Speed	17,365 ft/min	18,142 ft/min	18,809 ft/min
Width	48 in	52 in	61 in
ENGINE			
Fuel Tank	3.8 gal	3.8 gal	3.8 gal
Horsepower	20 hp	22 hp	24 hp
Engine Model	Kawasaki FT651V	Kawasaki FT691V	Kawasaki FT730V
WEIGHT			
Machine Weight	758 lbs	774 lbs	817 lbs
POWER/ELECTRICAL			
Clutch	125 ft-lb	125 ft-lb	125 ft-lb
Charging System	15 amp	15 amp	15 amp
TRANSMISSION			
Transmission Type	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3100 Hydrostatic Transaxles	HG ZT-3100 Hydrostatic Transaxles
Oil Capacity	4 qt	4 qt	4 qt
Travel Speed	8 mph	8 mph	8 mph
Travel Speed - Reverse	3.5 mph	3.5 mph	3.5 mph
WHEELS			
Drive Wheel Size	22 x 11.0-10	22 x 11.0-10	22 x 11.0-10
Caster Arm Attachment	Welded to frame	Welded to frame	Welded to frame
Front Caster Wheel Size	13 x 6.5-6	13 x 6.5-6	13 x 6.5-6
FRAME			
Length	80 in	80 in	81.9 in
Front and Rear	1.5 x 2.5-inch steel tubing; welded steel reinforced frame	1.5 x 2.5-inch steel tubing; welded steel reinforced frame	Welded 7-gauge Steel; 1.5 x 2.5 in steel tubing
SEAT			
Seat	High-back, spring suspension seat	High-back, spring suspension seat	High-back, spring suspension seat
Fore-Aft Adjustment	Seat slide lever	Seat slide lever	Seat slide lever