SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO ROUND TOP 10K

	6 x 12	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20
Model #	H7212TRT-100	H8412TRT-100	H8414TRT-100	H8416TRT-100	H8418TRT-100	H8420TRT-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight		2100	2280	2400	2695	2770
Payload		7800	7620	7500	7205	7130
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube				6" x 2" Steel Tube	
Front Profile	Round					
Frame	4" x 2" Steel Tube				6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	78"	84"				
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	Piedmont .080" Composite Panels	.080" Composite Panels				
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST225/75R15D 8-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening		80				
Width Rear Opening		78				
Deck Height		19			21	
Height Overall		103				
Deck Length		153	177	201	225	249
Width Interior		81				
Length Interior Box		153	177	201	225	249
DIMENSIONS						
Overall Length		192	216	242	266	290
Deck Length		153	177	201	225	249
Deck Width		81				
Deck Height		19			21	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8 x 14	8 x 16	8 x 18	8 x 20	8.5 x 16	8.5 x 18
Model #	H9614TRT-100	H9616TRT-100	H9618TRT-100	H9620TRT-100	H10116TRT-100	H10118TRT-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight	2450	2570	2850	3010	2850	3150
Payload	7450	7330	7050	6890	7050	6750
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Triple Tube	6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted					
Front Profile	Round					
Frame	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Tube	6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Integrated Step(s)	Interior Recessed					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.080" Composite Panels					
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST225/75R15D 8-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	80					
Width Rear Opening		90				
Deck Height		23				
Height Overall	103					
Deck Length		201	225	249	201	225
Width Interior			93		98.5	
Width Between Fender		82				
Length Interior Box		201	225	249	201	225
DIMENSIONS						
Overall Length		246	270	294	246	270
Deck Length		201	225	249	201	225
Deck Width			93		98.5	
Deck Height		23				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8.5 x 20
Model #	H10120TRT-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5200
Curb Weight	3200
Payload	6700
CHASSIS	
Coupler	2-5/16" A-Frame, Posi-Lock
Tongue	6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted
Front Profile	Round
Frame	6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center
Roof Bows	Galvanized Steel Tube, 24" On-Center
Wall Posts	Steel Tube, 24" On-Center
Standard Interior Height	84"
Ramp(s)	400 Series with Assist
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock
Integrated Step(s)	Interior Recessed
Hubs	Easy Lube
Protective Coating(s)	Polyethylene Vapor Barrier
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Exterior Finish	.080" Composite Panels
Stone Guard	24" ATP
Roof	Round Top
Tires	ST225/75R15D 8-PLY
Vents	Sidewall Airflow
Wiring	Enclosed in Conduit
Exterior Lights	Full LED, DOT Compliant
Height Rear Opening	80
Width Rear Opening	90
Deck Height	23
Height Overall	103
Deck Length	249
Width Interior	98.5
Width Between Fender	82
Length Interior Box	249
DIMENSIONS	
Overall Length	294
Deck Length	249
Deck Width	98.5
Deck Height	23

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO ROUND TOP VNOSE 10K

	6 x 14	7 x 12	7 x 14	7 x 16	7 x 18	7 x 20
Model #	H7214TRTV-100	H8412TRTV-100	H8414TRTV-100	H8416TRTV-100	H8418TRTV-100	H8420TRTV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight			2350	2500	2890	2870
Payload			7550	7400	7010	7030
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube				6" x 2" Steel Tube	
Frame	4" x 2" Steel Tube				6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	78"	84"				
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	Piedmont .080" Composite Panels	.080" Composite Panels				
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST225/75R15D 8-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening		80				
Height Overall		103				

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8 x 16	8 x 18	8 x 20	8.5 x 14	8.5 x 16	8.5 x 18
Model #	H9616TRTV-100	H9618TRTV-100	H9620TRTV-100	H10114TRTV-100	H10116TRTV-100	H10118TRTV-100
CAPACITIES						
GVWR (lbs)	9900					
GAWR (lbs/axle)	5200					
Curb Weight	2650	2850	3070	2870	2950	2850
Payload	7250	7050	6830	7030	6950	7050
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube	6" x 2" Steel Tube		4" x 2" Steel Triple Tube		6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted					
Frame	4" x 2" Steel Tube	6" x 2" Steel Tube		4" x 2" Steel Tube		6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Integrated Step(s)	Interior Recessed					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.080" Composite Panels					
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST225/75R15D 8-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	80					
Height Overall	103					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8.5 x 20
Model #	H10120TRTV-100
CAPACITIES	
GVWR (lbs)	9900
GAWR (lbs/axle)	5200
Curb Weight	3280
Payload	6620
CHASSIS	
Coupler	2-5/16" A-Frame, Posi-Lock
Tongue	6" x 2" Steel Triple Tube
Tongue Jack	2K Coupler Mounted
Frame	6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center
Roof Bows	Galvanized Steel Tube, 24" On-Center
Wall Posts	Steel Tube, 24" On-Center
Standard Interior Height	84"
Ramp(s)	400 Series with Assist
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock
Integrated Step(s)	Interior Recessed
Hubs	Easy Lube
Protective Coating(s)	Polyethylene Vapor Barrier
Flooring	3/4" Engineered Wood
Interior Walls	Engineered Wood
Exterior Finish	.080" Composite Panels
Stone Guard	24" ATP
Roof	Round Top
Tires	ST225/75R15D 8-PLY
Vents	Sidewall Airflow
Wiring	Enclosed in Conduit
Exterior Lights	Full LED, DOT Compliant
Height Rear Opening	80
Height Overall	103

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO ROUND TOP 14K

	7 x 14	7 x 16	7 x 18	7 x 20	8 x 16	8 x 18
Model #	H8414TRT-140	H8416TRT-140	H8418TRT-140	H8420TRT-140	H9616TRT-140	H9618TRT-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight		3050	3070	3200	2850	
Payload		10950	10930	10800	11150	
CHASSIS						
Coupler	2-5/16" Adjustable					
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	7K Drop Leg, Set-Back					
Front Profile	Round					
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Standard Interior Height	84"					
Ramp(s)					400 Series with Assist	
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Integrated Step(s)					Drop Down Side Step (1 on each side)	
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.080" Composite Panels					
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST235/80R16E 10-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	80					
Height Overall	103					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8 x 20	8.5 x 16	8.5 x 18	8.5 x 20
Model #	H9620TRT-140	H10116TRT-140	H10118TRT-140	H10120TRT-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	3320	3050	3500	3250
Payload	10680	10950	10500	10750
CHASSIS				
Coupler	2-5/16" Adjustable			
Tongue	6" x 2" Steel Triple Tube			
Tongue Jack	7K Drop Leg, Set-Back			
Front Profile	Round			
Frame	6" x 2" Steel Tube			
Crossmembers	Steel Formed Channel, 16" On-Center			
Roof Bows	Galvanized Steel Tube, 16" On-Center			
Wall Posts	Steel Tube, 16" On-Center			
Standard Interior Height	84"			
Ramp(s)	400 Series with Assist			
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock			
Integrated Step(s)	Drop Down Side Step (1 on each side)			
Hubs	Easy Lube			
Protective Coating(s)	Polyethylene Vapor Barrier			
Flooring	3/4" Engineered Wood			
Interior Walls	Engineered Wood			
Exterior Finish	.080" Composite Panels			
Stone Guard	24" ATP			
Roof	Round Top			
Tires	ST235/80R16E 10-PLY			
Vents	Sidewall Airflow			
Wiring	Enclosed in Conduit			
Exterior Lights	Full LED, DOT Compliant			
Height Rear Opening	80			
Height Overall	103			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO ROUND TOP VNOSE 14K

	7 x 14	7 x 16	7 x 20	8 x 16	8 x 18	8 x 20
Model #	H8414TRTV-140	H8416TRTV-140	H8420TRTV-140	H9616TRTV-140	H9618TRTV-140	H9620TRTV-140
CAPACITIES						
GVWR (lbs)	14000					
GAWR (lbs/axle)	7000					
Curb Weight			3150	2930	3250	3400
Payload			10850	11070	10750	10600
CHASSIS						
Coupler	2-5/16" Adjustable					
Tongue	6" x 2" Steel Triple Tube			6" x 2" Steel Triple Tube		
Tongue Jack	7K Drop Leg, Set-Back					
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 16" On-Center					
Wall Posts	Steel Tube, 16" On-Center					
Standard Interior Height	84"					
Ramp(s)				400 Series with Assist		
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Integrated Step(s)				Drop Down Side Step (1 on each side)		
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.080" Composite Panels					
Stone Guard	24" ATP					
Roof	.030 Aluminum Sheet, Round Top					
Tires	ST235/80R16E 10-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	80					
Height Overall	103					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8.5 x 16	8.5 x 18	8.5 x 20
Model #	H10116TRTV-140	H10118TRTV-140	H10120TRTV-140
CAPACITIES			
GVWR (lbs)	14000		
GAWR (lbs/axle)	7000		
Curb Weight	3190		3450
Payload	10810		10550
CHASSIS			
Coupler	2-5/16" Adjustable		
Tongue	6" x 2" Steel Triple Tube		
Tongue Jack	7K Drop Leg, Set-Back		
Frame	6" x 2" Steel Tube		
Crossmembers	Steel Formed Channel, 16" On-Center		
Roof Bows	Galvanized Steel Tube, 16" On-Center		
Wall Posts	Steel Tube, 16" On-Center		
Standard Interior Height	84"		
Ramp(s)	400 Series with Assist		
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock		
Integrated Step(s)	Drop Down Side Step (1 on each side)		
Hubs	Easy Lube		
Protective Coating(s)	Polyethylene Vapor Barrier		
Flooring	3/4" Engineered Wood		
Interior Walls	Engineered Wood		
Exterior Finish	.080" Composite Panels		
Stone Guard	24" ATP		
Roof	.030 Aluminum Sheet, Round Top		
Tires	ST235/80R16E 10-PLY		
Vents	Sidewall Airflow		
Wiring	Enclosed in Conduit		
Exterior Lights	Full LED, DOT Compliant		
Height Rear Opening	80		
Height Overall	103		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

SPECIFICATIONS -CARGO STEEL ENCLOSED
HH SERIES CARGO ROUND TOP 07K

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	7 x 18
Model #	H7212TRT-070	H7214TRT-070	H8412TRT-070	H8414TRT-070	H8416TRT-070	H8418TRT-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight		1770	1850	2050	2180	2545
Payload		5230	5150	4950	4820	4455
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube					6" x 2" Steel Tube
Front Profile	Round					
Frame	4" x 2" Steel Tube					6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	78"		84"			
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	Piedmont .080" Composite Panels		.080" Composite Panels			
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST205/75R15C 6-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening			80			
Width Rear Opening			78			
Deck Height				18		20
Height Overall			103			
Deck Length			153	177	201	225
Width Interior			81			
Length Interior Box			153	177	201	225
DIMENSIONS						
Overall Length			192	216	242	266
Deck Length			153	177	201	225
Deck Width			81			
Deck Height				18		20

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	7 x 20	8 x 14	8 x 16	8 x 18	8 x 20	8.5 x 16
Model #	H8420TRT-070	H9614TRT-070	H9616TRT-070	H9618TRT-070	H9620TRT-070	H10116TRT-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2570	2310	2350	2670	2800	2710
Payload	4430	4690	4650	4330	4200	4290
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	6" x 2" Steel Tube	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Triple Tube
Tongue Jack		2K Coupler Mounted				
Front Profile	Round					
Frame	6" x 2" Steel Tube	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)		400 Series with Assist				
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Integrated Step(s)		Interior Recessed				
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.080" Composite Panels					
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST205/75R15C 6-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	80					
Width Rear Opening	78		90			
Deck Height	20		22			
Height Overall	103					
Deck Length	249		201	225	249	201
Width Interior	81		93			98.5
Width Between Fender			82			
Length Interior Box	249		201	225	249	201
DIMENSIONS						
Overall Length	290		246	270	294	246
Deck Length	249		201	225	249	201
Deck Width	81		93			98.5
Deck Height	20		22			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8.5 x 18	8.5 x 20
Model #	H10118TRT-070	H10120TRT-070
CAPACITIES		
GVWR (lbs)	7000	
GAWR (lbs/axle)	3500	
Curb Weight	2750	2950
Payload	4250	4050
CHASSIS		
Coupler	2-5/16" A-Frame, Posi-Lock	
Tongue	6" x 2" Steel Triple Tube	
Tongue Jack	2K Coupler Mounted	
Front Profile	Round	
Frame	6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center	
Roof Bows	Galvanized Steel Tube, 24" On-Center	
Wall Posts	Steel Tube, 24" On-Center	
Standard Interior Height	84"	
Ramp(s)	400 Series with Assist	
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock	
Integrated Step(s)	Interior Recessed	
Hubs	Easy Lube	
Protective Coating(s)	Polyethylene Vapor Barrier	
Flooring	3/4" Engineered Wood	
Interior Walls	Engineered Wood	
Exterior Finish	.080" Composite Panels	
Stone Guard	24" ATP	
Roof	Round Top	
Tires	ST205/75R15C 6-PLY	
Vents	Sidewall Airflow	
Wiring	Enclosed in Conduit	
Exterior Lights	Full LED, DOT Compliant	
Height Rear Opening	80	
Width Rear Opening	90	
Deck Height	22	
Height Overall	103	
Deck Length	225	249
Width Interior	98.5	
Width Between Fender	82	
Length Interior Box	225	249
DIMENSIONS		
Overall Length	270	294
Deck Length	225	249
Deck Width	98.5	
Deck Height	22	

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

SPECIFICATIONS -CARGO STEEL ENCLOSED

HH SERIES CARGO ROUND TOP VNOSE 07K

	6 x 12	6 x 14	7 x 12	7 x 14	7 x 16	7 x 18
Model #	H7212TRTV-070	H7214TRTV-070	H8412TRTV-070	H8414TRTV-070	H8416TRTV-070	H8418TRTV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	1770	1950	1930	2125	2230	2450
Payload	5230	5050	5070	4875	4770	4550
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	4" x 2" Steel Tube					6" x 2" Steel Tube
Frame	4" x 2" Steel Tube					6" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	78"		84"			
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	Piedmont .080" Composite Panels		.080" Composite Panels			
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST205/75R15C 6-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening			80			
Height Overall			103			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	7 x 20	8 x 14	8 x 16	8 x 18	8 x 20	8.5 x 14
Model #	H8420TRTV-070	H9614TRTV-070	H9616TRTV-070	H9618TRTV-070	H9620TRTV-070	H10114TRTV-070
CAPACITIES						
GVWR (lbs)	7000					
GAWR (lbs/axle)	3500					
Curb Weight	2470	2530	2430	2750	2880	2620
Payload	4530	4470	4570	4250	4120	4380
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					
Tongue	6" x 2" Steel Tube	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Triple Tube
Tongue Jack		2K Coupler Mounted				
Frame	6" x 2" Steel Tube	4" x 2" Steel Tube		6" x 2" Steel Tube		4" x 2" Steel Tube
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					
Wall Posts	Steel Tube, 24" On-Center					
Standard Interior Height	84"					
Ramp(s)		400 Series with Assist				
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock					
Integrated Step(s)		Interior Recessed				
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Exterior Finish	.080" Composite Panels					
Stone Guard	24" ATP					
Roof	Round Top					
Tires	ST205/75R15C 6-PLY					
Vents	Sidewall Airflow					
Wiring	Enclosed in Conduit					
Exterior Lights	Full LED, DOT Compliant					
Height Rear Opening	80					
Height Overall	103					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8.5 x 16	8.5 x 18	8.5 x 20
Model #	H10116TRTV-070	H10118TRTV-070	H10120TRTV-070
CAPACITIES			
GVWR (lbs)	7000		
GAWR (lbs/axle)	3500		
Curb Weight	2790		2830
Payload	4210		4170
CHASSIS			
Coupler	2-5/16" A-Frame, Posi-Lock		
Tongue	4" x 2" Steel Triple Tube	6" x 2" Steel Triple Tube	
Tongue Jack	2K Coupler Mounted		
Frame	4" x 2" Steel Tube	6" x 2" Steel Tube	
Crossmembers	Steel Formed Channel, 16" On-Center		
Roof Bows	Galvanized Steel Tube, 24" On-Center		
Wall Posts	Steel Tube, 24" On-Center		
Standard Interior Height	84"		
Ramp(s)	400 Series with Assist		
Side Door	36" Wide Flush Lock, Aluminum Holdback, Barlock		
Integrated Step(s)	Interior Recessed		
Hubs	Easy Lube		
Protective Coating(s)	Polyethylene Vapor Barrier		
Flooring	3/4" Engineered Wood		
Interior Walls	Engineered Wood		
Exterior Finish	.080" Composite Panels		
Stone Guard	24" ATP		
Roof	Round Top		
Tires	ST205/75R15C 6-PLY		
Vents	Sidewall Airflow		
Wiring	Enclosed in Conduit		
Exterior Lights	Full LED, DOT Compliant		
Height Rear Opening	80		
Height Overall	103		

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC