SPECIFICATIONS 2000 SERIES








	MODEL (2000 SERIES)	CT2025 HST	CT2025 MST	CT2035 HST	CT2535 HST	CT2040 HST	CT2540 HST
ENGINE	Type	Diesel	Diesel	Diesel	Diesel	Diesel	Diesel
	Gross Horsepower	24.5 hp (18.2 kW)	24.5 hp (18.2 kW)	34.9 hp (26.0 kW)	34.9 hp (26.0 kW)	39.6 hp (29.5 kW)	39.6 hp (29.5 kW)
	No. of Cylinders	3	3	3	3	3	3
	Total Displacement	100 cu. in. (1.6 L)	100 cu. in. (1.6 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)	111.4 cu. in. (1.8 L)
	Fuel Tank Capacity	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)	9.0 gal. (34.1 L)
FRONT-END LOADER	Lift Capacity at Max. Height*	1369 lb. (621 kg)	1369 lb. (621 kg)	1389 lb. (630 kg)	1389 lb. (630 kg)	1389 lb. (630 kg)	1389 lb. (630 kg)
	Max. Lift Height	95.0 in. (2413 mm)	95.0 in. (2413 mm)	99.4 in. (2524 mm)	99.4 in. (2524 mm)	99.4 in. (2524 mm)	99.4 in. (2524 mm)
	Standard Bucket Width	60.0 in. (1524 mm)	60.0 in. (1524 mm)	60.0 in. (1524 mm)	60.0 in. (1524 mm)	60.0 in. (1524 mm)	60.0 in. (1524 mm)
3-POINT, PTO & HYDRAULICS	3-Point Hitch	Category 1	Category 1	Category 1	Category 1	Category 1	Category 1
	3-Point Lift Capacity**	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)	1631 lb. (740 kg)
	3-Point Link Stabilizers	Turnbuckle	Turnbuckle	Turnbuckle	Telescoping	Turnbuckle	Telescoping
	Lift Control Type	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System	Hydraulic Position Control System
	Lifting Rod	Turnbuckle	Turnbuckle	Turnbuckle	Crank	Turnbuckle	Crank
	Lower Links	Fixed	Fixed	Fixed	Telescopic	Fixed	Telescopic
	Mid-PTO	Optional: 1976 rpm	Optional: 1976 rpm	Optional: 1988 rpm	Optional: 1988 rpm	Optional: 1988 rpm	Optional: 1988 rpm
	PTO Horsepower	21.8 hp (16.3 kW)	22.2 hp (16.6 kW)	29.4 hp (21.9 kW)	29.4 hp (21.9 kW)	31.9 hp (23.8 kW)	31.9 hp (23.8 kW)
	Rear Hydraulics	2 Pairs Opt	2 Pairs Opt	2 Pairs Opt	2 Pairs Std	2 Pairs Opt	2 Pairs Std
	Rear PTO	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm	540 rpm
	Rear PTO System	Live	Live	Live	Independent	Live	Independent
	Total Hydraulic Pump Capacity	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)	11.4 gpm (42.9 L/min.)
DRIVE SYSTEM	Transmission	3-Range HST	9F x 3R Manual	3-Range HST	3-Range HST	3-Range HST	3-Range HST
	Brakes	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc	Wet Multi-Disc
	Rear Differential Lock	Std	Std	Std	Std	Std	Std
	Four-Wheel Drive	Std	Std	Std	Std	Std	Std
TRAVEL SPEEDS	Forward (w/ industrial tires)	9.4 mph (15.1 km/hr.)	9.2 mph (14.8 km/hr.)	14.0 mph (22.5 km/hr.)	14.0 mph (22.5 km/hr.)	14.0 mph (22.5 km/hr.)	14.0 mph (22.5 km/hr.)
	Reverse (w/ industrial tires)	6.5 mph (10.4 km/hr.)	6.0 mph (9.6 km/hr.)	9.7 mph (15.6 km/hr.)	9.7 mph (15.6 km/hr.)	9.7 mph (15.6 km/hr.)	9.7 mph (15.6 km/hr.)
DIMENSIONS	Overall Length (w/ 3 pt.)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)	120.9 in. (3070 mm)
	Overall Width (w/ industrial tires)	62.4 in. (1584 mm)	62.4 in. (1584 mm)	62.4 in. (1584 mm)	62.4 in. (1584 mm)	62.4 in. (1584 mm)	62.4 in. (1584 mm)
	Overall Height	92.2 in. (2341 mm)	92.2 in. (2341 mm)	92.2 in. (2341 mm)	91.0 in. (2311 mm)	92.2 in. (2341 mm)	91.0 in. (2311 mm)
	Wheelbase	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)	65.7 in. (1670 mm)
	Ground Clearance	11.7 in. (297 mm)	11.7 in. (297 mm)	11.7 in. (297 mm)	11.7 in. (297 mm)	11.7 in. (297 mm)	11.7 in. (297 mm)
	Weight	2634 lb. (1195 kg)	2634 lb. (1195 kg)	3005 lb. (1363 kg)	3585 lb. (1626 kg)	3005 lb. (1363 kg)	3585 lb. (1626 kg)
STEERING	Type	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
	Inside Turning Radius	96.5 in. (2450 mm)	96.5 in. (2450 mm)	96.5 in. (2450 mm)	106.3 in. (2700 mm)	96.5 in. (2450 mm)	106.3 in. (2700 mm)
	Tilt Steering Wheel	—	—	—	Std	—	Std
FEATURES	Adjustable Seat	Std	Std	Std	Std	Std	Std
	Cup Holder	Std	Std	Std	Std	Std	Std
	Glow Plug Engine Preheat	Std	Std	Std	Std	Std	Std
	Toolbox	Opt	Opt	Opt	Std	Opt	Std
	Head Lights/Tail Lights/ Brake Lights	Std	Std	Std	Std	Std	Std
	Cruise Control	Opt	—	Opt	Std	Opt	Std
	Spark Arrestor Muffler	Opt	Std	Std	Std	Std	Std
	Horn/Hazard Flasher/ Turn Signals	Std	Std	Std	Std	Std	Std
	Rear Working Light	Opt	Opt	Opt	Std	Opt	Std
	Side Mirror	Opt	Opt	Opt	Std	Opt	Std
	Enclosed Cab With Heat/AC	—	—	—	Std	—	Std

**Loader lift capacity to maximum height at bucket pivot pins.*

***Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.*