MIDSOTA®

SPECIFICATIONS -MIDSOTA OPENS

MIDSOTA BEAM ST EQUIPMENT 15.4K

	82 x	82 x	82 x	82 x
Model #	N-BST22-154	N-BST20-154	N-BST18-154	N-BST24-154
CAPACITIES				
GVWR (lbs)	15400			
GAWR (lbs/axle)	7000			
Curb Weight	3680	3500	3320	3860
Payload	11720	11900	12080	11540
CHASSIS				
Coupler	2-5/16" 4-Bolt Flat Plate			
Tongue	8" Flange, 15 lb/ft I-Beam			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	8", 15 lb/ft I-Beam			
Crossmembers	16" Crossmember Spacing, Rolled Grade 50 3" Steel Channel			
Beavertail	3' Cleated			
Ramp(s)	5' Tall Spring Assist Stand-Up with Adjustable Support Legs			
Axle	(2) 7000 lb. Drop Slipper Spring Brake			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Tie Downs	(6) 3/4" D-Rings, Stake Pockets and Rub Rail			
Exterior Lights	Full LED, DOT Compliant			
Dovetail	3' Self Cleaning			
Decking	2" Pressure Treated Pine			
Exterior Storage	A-Frame Steel Lockable Toolbox, Spare Tire Carrier			
Coupler Height	11.5 - 19.5			
Deck Height	21			
DIMENSIONS				
Overall Length	296			
Deck Height	21			
Coupler Height	11.5 - 19.5			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

 © 2026 Novae LLC

MIDSOTA®

SPECIFICATIONS -MIDSOTA OPENS

MIDSOTA BEAM ST EQUIPMENT 17.6K

	82 x	82 x	82 x	82 x
Model #	N-BST20-176	N-BST22-176	N-BST24-176	N-BST18-176
CAPACITIES				
GVWR (lbs)	17600			
GAWR (lbs/axle)	8000			
Curb Weight	4120	4300	4480	3940
Payload	13480	13300	13120	13660
CHASSIS				
Coupler	2-5/16" Adjustable EZ Latch 4-Bolt Flat Plate			
Tongue	8" Flange, 15 lb/ft I-Beam			
Tongue Jack	12K Drop Leg, Set-Back			
Frame	8", 15 lb/ft I-Beam			
Crossmembers	16" Crossmember Spacing, Rolled Grade 50 3" Steel Channel			
Beavertail	3' Cleated			
Ramp(s)	5' Tall Spring Assist Stand-Up with Support Legs			
Axle	(2) 8000 lb. Slipper Spring Brake			
Tires	215/75R17.5J 18-PLY			
Wheels	17.5", 8-Lug Steel			
Tie Downs	(6) 3/4" D-Rings, Stake Pockets and Rub Rail			
Dovetail	3' Self Cleaning			
Decking	2" Pressure Treated Pine			
Exterior Storage	A-Frame Steel Lockable Toolbox, Spare Tire Carrier			
Coupler Height	11.5 - 19.5			
Deck Height	21			
DIMENSIONS				
Overall Length	296			
Deck Height	21			
Coupler Height	11.5 - 19.5			

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC