Neal Trailers

Phone: +18126893131
3115 N US 421
Osgood, Indiana
Email: travisneal1@aol.com

2026 Diamond C Trailers FMAX212 FMAX212 2.0 Engineered Beam 25.9K Hydraulic Doveta

Type	Trailer or Truck Bed	**Category**	Flatbed Trailer
Stock#	14706	**VIN**	46UDF4427T1314706
Location	Neal Trailers	**Year**	2026
Status	Available	**Condition**	New
Manufacturer	Diamond C Trailers	**Model**	FMAX212 FMAX212 2.0 Engineered Beam 25.9K Hydraulic Doveta
Color	Brown		

https://nealmotor.com/unit/2026-diamond-c-trailers-fmax212-fmax212-2-0-engineered-beam-25-9k-hydraulic-doveta-1308482

Price: $43,999.00

Description

Component
Description
Model
FMAX212 2.0 Engineered Beam 25.9K Hydraulic Dovetail Trailer
Frame Size
44' × 102" deck width
Frame
Engineered beam frame with 3" I-beam crossmembers on 16" centers for extreme-duty strength
Axles
Two 12,000 lb axles with electric drum brakes and ABS anti-lock braking system (24,000 lb axle capacity total)
Neck
12" engineered gooseneck neck for improved strength and load distribution
Coupler

30K Shocker Hitch with 2-5/16" ball (square mount) for cushioned towing performance
Suspension
Heavy-duty adjustable suspension system for optimized load handling
Axle Configuration
60" spread axle setup for improved stability and weight distribution
Dovetail
12' fully automatic hydraulic dovetail system with 5-amp charger system
Dovetail Surface
Blackwood runner system (optional Aluma Trax aluminum floor upgrade available)
Floor
2" treated wood floor (Aluma Trax aluminum flooring upgrade available for full 44')
Winch Mount
Integrated gooseneck winch mounting tray for secure equipment recovery
Jack System
Dual 20,000 lb hydraulic jacks for maximum lifting power and stability
Hydraulic Capacity
25.9K rated hydraulic system for dovetail operation
Battery System
Lithium battery upgrade for improved hydraulic performance and longevity
Storage Boxes
Two (2) 14" × 14" × 42" under-slung storage boxes
Spare Tire Mount
Retractable under-frame cable winch spare tire carrier
Slide Track System
Passenger-side slide track with welded ratchet (full 44' length)
Tie-Downs
Fourteen (14) additional 5/8" heavy-duty D-ring tie-down points
Sway Control
Standard sway control pipe for towing stability
Tires
ST235/80R16 dual 14-ply radial tires with aluminum outer wheels
Spare Tire
Matching ST235/80R16 dual 14-ply radial spare on 8-hole black wheel
Lighting
Full LED lighting package for visibility and safety
Clearance Lights
Extra clearance lighting (8 pairs) for enhanced visibility on long hauls
Paint
Mocha Metallic finish
Decals
FMAX212 branding package
