Neal Trailers

Phone: +18126893131
3115 N US 421
Osgood, Indiana
Email: travisneal1@aol.com



2026 Diamond C Trailers Unknown GTU L16X83

Type	Trailer or Truck Bed	**Category**	Utility Trailer
Stock#	14140	**VIN**	46UFU1622T1314140
Location	Neal Trailers	**Year**	2026
Status	Available	**Condition**	New
Manufacturer	Diamond C Trailers	**Model**	Unknown GTU L16X83
Color	Gray		

https://nealmotor.com/unit/2026-diamond-c-trailers-unknown-gtu-l16x83-1308554

Price: $6,999.00

Description

Component
Description
Coupler, 2" - 10K Demco EZ-Latch (Adjustable Channel)
Fits a 2-inch hitch ball, rated for 10,000 lbs. The adjustable channel allows the coupler height to be changed. The Demco EZ-Latch automatically latches when lowered onto the hitch ball.
Tongue, Tandem Utility
Heavy-duty trailer tongue designed for a tandem-axle utility trailer.

Jack, 7K Drop Leg Jack
Trailer jack rated for 7,000 lbs with a drop leg for quicker setup.
Ramp Gate, 48" Bi-Fold (2" Square Tube)
48-inch tall folding rear loading gate built from 2-inch square tubing. Folds in half to reduce wind resistance.
Fender, 12-ga Smooth, Weld-On
Welded steel fenders made from heavy 12-gauge smooth steel.
Floor, 2" Treated
2-inch pressure-treated wood decking.
Standard Stake Pockets (5 Total)
Five stake pockets for removable sideboards or tie-down points.
Tires, ST205/75R15 Radial, 5-Hole Aluminum
Trailer radial tires on 15-inch aluminum wheels with a 5-lug bolt pattern.
Spare, ST205/75R15 Radial, 5-Hole Aluminum
Matching spare tire and aluminum wheel.
Paint, Carbon Metallic Gray
Trailer painted in carbon metallic gray.
Lights, All LED
LED running, brake, turn, and marker lights.
Decals, GTU
GTU branding/graphics package.
Frame Size, L16X83
Trailer measures 16 feet long by 83 inches wide between the fenders (approximately a 7-foot-wide deck).
Axles, 2 × 3,500-lb Straight with Electric Brakes
Two 3,500-lb axles, each equipped with electric brakes. Gross axle capacity is 7,000 lbs.
Suspension, 5-Leaf Slipper Springs
Heavy-duty slipper spring suspension with five leaves for durability and load carrying.
Frame, 4" Channel with 2" Channel Crossmembers on 24" Centers
Main frame uses 4-inch channel steel with 2-inch channel crossmembers spaced every 24 inches.
Spare Mount, Cable Winch (Under Frame, Retractable)
Spare tire stores underneath the trailer and is lowered/raised using a cable winch.
Top Rail, 2-3/8" Pipe, Expanded Metal Sides (L16)
Full-length expanded metal sides with a 2?-inch pipe top rail.
Storage, 10" × 13" Lockable Steel Tongue Box
Lockable toolbox mounted on the tongue for straps, chains, tools, etc.
Overall specificationsDeck size: 16' × 83"
Axles: Tandem 3,500 lb (7,000 lb total axle capacity)
Brakes: Electric brakes on both axles
Floor: 2" treated lumber
Rear gate: 48" bi-fold ramp
Sides: Expanded metal with pipe top rail
Wheels: Aluminum with matching spare
Lighting: Full LED
Color: Carbon Metallic Gray
Extras: Lockable tongue box and under-frame retractable spare tire carrier
This is a fairly well-equipped utility trailer suitable for hauling UTVs, compact tractors, zero-turn mowers, ATVs, small vehicles, building materials, and general equipment, with an expected 7,000-lb Gross Vehicle Weight Rating (GVWR) if the frame and coupler are rated accordingly. The trailer's actual payload would typically be in the neighborhood of 5,000–5,500 lbs, depending on its

empty weight.