SPECIFICATIONS -CARGO STEEL ENCLOSED
HH SERIES CAR HAULER FLAT TOP

	8.5 x 20	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28	8.5 x 20
Model #	H10120FTCHV-100	H10122FTCHV-100	H10124FTCHV-100	H10126FTCHV-100	H10128FTCHV-100	H10120FTCHV-140
CAPACITIES						
GVWR (lbs)	9900					14000
GAWR (lbs/axle)	5200					7000
Curb Weight	3600	3470	3620	3800	3950	3650
Payload	6300	6430	6280	6100	5950	10350
CHASSIS						
Coupler	2-5/16" A-Frame, Posi-Lock					2-5/16" Adjustable
Tongue	6" x 2" Steel Triple Tube					
Tongue Jack	2K Coupler Mounted					7K Drop Leg, Set-Back
Front Profile	V-Nose					
Frame	6" x 2" Steel Tube					
Crossmembers	Steel Formed Channel, 16" On-Center					
Roof Bows	Galvanized Steel Tube, 24" On-Center					Galvanized Steel Tube, 16" On-Center
Wall Posts	Steel Tube, 24" On-Center					Steel Tube, 16" On-Center
Ramp(s)	400 Series with Assist					
Side Door	36" Wide Flush Lock, Aluminum Holdback					
Axle	(2) 5200 lb. Drop Spring Brake					(2) 7000 lb. Drop Spring Brake
Hubs	Easy Lube					
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel					
Flooring	3/4" Engineered Wood					
Interior Walls	Engineered Wood					
Interior Trim	Aluminum H-Channel Wall Transitions					
Exterior Finish	.030" Aluminum					
Exterior Fastening	VHB Bonded (Screwless)					
Stone Guard	24" ATP					
Roof	Flat Top .024 Aluminum Sheeted					
Tires	ST225/75R15D 8-PLY					ST235/80R16E 10-PLY
Wheels	15", 6-Lug Steel					16", 8-Lug Steel
Tie Downs	(4) Floor Mounted, Non-swivel Recessed D-Rings					
Wiring	Enclosed in Conduit					
Interior Lights	(2) LED Dome Lights, Wall Mount					
Exterior Lights	Full LED, DOT Compliant					
Dovetail	4' Interior					
Height Rear Opening	68		68			68
Width Rear Opening	95		95			95
Deck Height	22		22		22	23
Height Overall	98		98		98	99
Deck Length	267		315		363	267
Width Interior	98.5		98.5			98.5
Width Between Fender	82		82			82
Length Interior Box	267		315		363	267
DIMENSIONS						
Overall Length	301		349		397	301
Deck Length	267		315		363	267
Deck Width	98.5		98.5			98.5
Deck Height	22		22		22	23

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC

	8.5 x 22	8.5 x 24	8.5 x 26	8.5 x 28
Model #	H10122FTCHV-140	H10124FTCHV-140	H10126FTCHV-140	H10128FTCHV-140
CAPACITIES				
GVWR (lbs)	14000			
GAWR (lbs/axle)	7000			
Curb Weight	3930	4240		4150
Payload	10070	9760		9850
CHASSIS				
Coupler	2-5/16" Adjustable			
Tongue	6" x 2" Steel Triple Tube			
Tongue Jack	7K Drop Leg, Set-Back			
Front Profile	V-Nose			
Frame	6" x 2" Steel Tube			
Crossmembers	Steel Formed Channel, 16" On-Center			
Roof Bows	Galvanized Steel Tube, 16" On-Center			
Wall Posts	Steel Tube, 16" On-Center			
Ramp(s)	400 Series with Assist			
Side Door	36" Wide Flush Lock, Aluminum Holdback			
Axle	(2) 7000 lb. Drop Spring Brake			
Hubs	Easy Lube			
Protective Coating(s)	Polyethylene Vapor Barrier, Textured Polyurea all Exposed Steel			
Flooring	3/4" Engineered Wood			
Interior Walls	Engineered Wood			
Interior Trim	Aluminum H-Channel Wall Transitions			
Exterior Finish	.030" Aluminum			
Exterior Fastening	VHB Bonded (Screwless)			
Stone Guard	24" ATP			
Roof	Flat Top .024 Aluminum Sheeted			
Tires	ST235/80R16E 10-PLY			
Wheels	16", 8-Lug Steel			
Tie Downs	(4) Floor Mounted, Non-swivel Recessed D-Rings			
Wiring	Enclosed in Conduit			
Interior Lights	(2) LED Dome Lights, Wall Mount			
Exterior Lights	Full LED, DOT Compliant			
Dovetail	4' Interior			
Height Rear Opening		68		68
Width Rear Opening		95		95
Deck Height		23		23
Height Overall		99		99
Deck Length		315		363
Width Interior		98.5		98.5
Width Between Fender		82		82
Length Interior Box		315		363
DIMENSIONS				
Overall Length		349		397
Deck Length		315		363
Deck Width		98.5		98.5
Deck Height		23		23

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC