SPECIFICATIONS 1000 SERIES





	MODEL	CT1021	CT1025
ENGINE	Type	Diesel	Diesel
	Gross Horsepower	21.0 hp (15.7 kW)	24.5 hp (18.3 kW)
	No. of Cylinders	3	3
	Total Displacement	61.5 cu. in. (1.0 L)	61.5 cu. in. (1.0 L)
	Fuel Tank Capacity	6.7 gal. (25.5 L)	6.7 gal. (25.5 L)
FRONT-END LOADER	Lift Capacity at Max. Height*	608 lb. (276 kg)	608 lb. (276 kg)
	Max. Lift Height	73.0 in. (1854 mm)	73.0 in. (1854 mm)
	Standard Bucket Width	48.0 in. (1219 mm)	48.0 in. (1219 mm)
3-POINT, PTO & HYDRAULICS	3-Point Hitch	Category 1 Limited	Category 1 Limited
	3-Point Lift Capacity**	700 lb. (318 kg)	700 lb. (318 kg)
	3-Point Link Stabilizers	Turnbuckle	Turnbuckle
	Lift Control Type	Hydraulic Position Control System	Hydraulic Position Control System
	Lifting Rod	Turnbuckle	Turnbuckle
	Lower Links	Rigid	Rigid
	Mid-PTO	Standard: 2200 rpm	Standard: 2200 rpm
	PTO Horsepower	16.3 hp (12.1 kW)	18.8 hp (14.0 kW)
	Rear Hydraulics (optional)	1 Pair	1 Pair
	Rear PTO	540 rpm	540 rpm
	Rear PTO System	Independent	Independent
	Total Hydraulic Pump Capacity	7.2 gpm (27.4 L/min.)	7.2 gpm (27.4 L/min.)
DRIVE SYSTEM	Transmission	2-Range HST	2-Range HST
	Brakes	Wet Multi-Disc	Wet Multi-Disc
	Rear Differential Lock	Std	Std
	Four-Wheel Drive	Std	Std
TRAVEL SPEEDS	Forward (w/ industrial tires)	11.1 mph (17.8 km/hr.)	11.1 mph (17.8 km/hr.)
	Reverse (w/ industrial tires)	7.6 mph (12.2 km/hr.)	7.6 mph (12.2 km/hr.)
DIMENSIONS	Overall Length (w/ 3 pt.)	99.3 in. (2522 mm)	99.3 in. (2522 mm)
	Overall Width (w/ industrial tires)	45.7 in. (1161 mm)	45.7 in. (1161 mm)
	Overall Height	87.6 in. (2225 mm)	87.6 in. (2225 mm)
	Wheelbase	55.1 in. (1400 mm)	55.1 in. (1400 mm)
	Ground Clearance	6.3 in. (160 mm)	6.3 in. (160 mm)
	Weight	1521 lb. (690 kg)	1521 lb. (690 kg)
STEERING	Type	Hydrostatic Power Steering	Hydrostatic Power Steering
	Inside Turning Radius	100.0 in. (2540 mm)	100.0 in. (2540 mm)
	Tilt Steering Wheel	—	—
FEATURES	Adjustable Seat	Std	Std
	Cup Holder	Std	Std
	Glow Plug Engine Preheat	Std	Std
	Toolbox	Std	Std
	Head Lights/Tail Lights/Brake Lights	Std	Std
	Cruise Control	Opt	Opt
	Spark Arrestor Muffler	Opt	Opt
	Horn/Hazard Flasher/Turn Signals	Std	Std
	Rear Working Light	Opt	Opt
	Dealer-Installed Cab With Heat	Opt	Opt

**Loader lift capacity to maximum height at bucket pivot pins.*

***Note: Hydraulic 3 pt. lift capacity will vary depending on lift point height.*



Machine: CT1021