SURE-TRAC

SPECIFICATIONS -UTILITY - STEEL

TUBE TOP UTILITY 3K

	5 x 8	5 x 10	6 x 10	6 x 12	7 x 12	7 x 14
Model #	ST-UTT6208-030	ST-UTT6210-030	ST-UTT7210-030	ST-UTT7212-030	ST-UTT8212-030	ST-UTT8214-030
CAPACITIES						
GVWR (lbs)	2990					
GAWR (lbs/axle)	3500					
Curb Weight	890	960	990	1115	1300	1420
Payload	2100	2030	2000	1875	1690	1570
CHASSIS						
Coupler	2" A-Frame					
Tongue	4" Steel Channel					
Tongue Jack	2K Set-Back					
Frame	3" x 2" x 3/16" Steel Angle					
Crossmembers	3" x 2" x 3/16" Steel Angle					
Ramp(s)	4' Fold-Flat Spring-Assist with Grab Handle, Self-Retained Gate Pins					
Axle	3500 lb. Spring Idler					
Hubs	Easy Lube					
Exterior Finish	Industrial Grade Polymer Finish					
Tires	ST205/75R15C 6-PLY					
Wheels	15", 5-Lug Steel					
Tie Downs	Stake Pockets					
Exterior Lights	Full LED, DOT Compliant					
Top Rail	2" x 2" Steel Tube					
Uprights	2" x 2" Steel Tube					
Sides	13" Tall					
Gate	56.8 x 48		66.8 x 48		76.8 x 48	
Decking	2" Pressure Treated Pine, Board Retainers					
Exterior Storage	Spare Tire Carrier					
Coupler Height	16					
Deck Height	21					
Width Between Fender	62		72		82	
Width Ramp	56.75		66.75		76.75	
Length Ramp	48					
DIMENSIONS						
Overall Length	142	166		190		214
Deck Height	21					
Coupler Height	16					

Features and Specifications subject to change without notice. Please contact your local dealer for confirmation.

© 2026 Novae LLC