

Taneytown, MD

Phone: +14107562430

115 York St

Taneytown, Maryland

Email: adam@hitchman.com



Ferris ISX2200Z 60" Commercial Zero Turn Mower, 31 HP Kawasaki EVO EFI

Type	Equipment	Category	Lawn Mowers
Stock#	T5902180	Location	Taneytown, MD
Year	2026	Status	Special Order
Condition	New	Manufacturer	Ferris
Model	ISX2200Z	Floor Width	60in / 5ft
Color	Red		

<https://thehitchmaninc.com/unit/ferris-isx2200z-60-commercial-zero-turn-mower-31-hp-kawasaki-evo-efi-631456>

Call for Price

Description

***Fleet pricing & additional discounts may be available at time of purchase. Please call us at (410)756-2430 for more information.

ISX™ 2200 Zero Turn Mowers

THE LEADER IN SUSPENSION TECHNOLOGY FOR TURF

Take productivity and comfort up a notch. The ISX™ 2200 boasts our most advanced suspension technology – ForeFront™ Suspension, ensuring operator comfort. A redesigned 2-belt iCD™+ cutting system (select models) delivers unrivaled cut quality and the heavy-duty Hydro-Gear® ZT-4400™ Transaxle drive system provides power and durability to get the job done.

- Engine BrandKawasaki® FX781V EVO
 - Engine Power Rating *30.5
 - Displacement (cc)822
 - PTOElectric
 - Cylinders2
 - StarterElectric
 - Fuel TypeGasoline
 - Fuel Tank Capacity (gal)11
 - Hour Meter/InstrumentationDual-function hour meter, fuel level gauge in each tank
 - Deck Size (in)60
 - Cutting Height (in)1.5 - 5
 - SpindlesCast-iron greaseable
 - Deck ConstructioniCD™+ Cutting System, 2-Belt
 - SuspensionForeFront™ Suspension System
 - TransmissionDual, commercial Hydro-Gear® ZT-4400™ Transaxles with 8.3" cooling fans
 - Drive Axles (in)1.375
 - Caster Tires (in)13 x 6.5-6
 - Drive Tires (in)24 x 12-12
 - Ground Speed-Fwd (mph)0-10
 - Ground Speed-Rev (mph)0-5
 - Overall Length (in)82.5
 - Overall Width (in) Deflector Down/Deflector Up74 / 65
 - Dry Weight (lbs)1302
 - Seat PackagePremium high-back Suspension Seat with adjustable arm rests, adjustable lumbar and back recline.
 - Certified Roll-over Protection System180° foldable
 - Controls / Safety GroupSeat activated engine kill, clutch safety switch, neutral and parking brake safety circuit/adjustable twin steering controls
 - Parking Brake / Safety CircuitHand operated Internal transaxle brake
 - Warranty (Engine) †3-Year limited manufacturer's warranty
 - Warranty (Balance of Machine) †4-Year limited warranty (48 months) or 500 hours, whichever occurs first. Unlimited hours during the first 2 years (24 months). Coil-over shocks and all suspension related components are covered for 5 years (60 months) unlimited hours. Coverage on other components varies, please see operator's manual for complete details.
 - Engine Configuration - Kawasaki®
-