Cottondale

Phone: +18503522151
3151 Main St
Cottondale, Florida
Email: trioakenterprise@gmail.com



2025 Husqvarna 395 XP Chainsaw

Type	Equipment	**Category**	Chainsaw
Stock#	HUS0026	**Location**	Cottondale
Year	2025	**Status**	Available
Condition	New	**Manufacturer**	Husqvarna
Model	395 XP		

https://www.ttsoutdoor.com/unit/2025-husqvarna-395-xp-chainsaw-943707

Call for Price

Description

OVERVIEW

Professional 94cc chainsaw built for the toughest forestry jobs
Choose one of the world's most capable and legendary chainsaws. The Husqvarna 395 XP is built for professional loggers and foresters. Excellent balance and a rugged handle design make this large saw easy to operate - even with longer guide bars. The aggressive clutch can handle the chainsaw's substantial power, while a wider clutch cover guarantees effective wood chip dispersal. Take your work to the highest level of performance with this trusted machine.

SPECIFICATIONS

32" Bar, .3/8" Pitch, .050" Gauge
SKU: 965 90 27-09
Engine

32" Bar, .3/8" Pitch, .050" Gauge
SKU: 965 90 27-09
Chain speed at max power: 64.3 fts
Cylinder displacement: 94 cm3
Output shaft power: 6.6 hp
Torque, max.: 5.9 Nm
Torque, max. at rpm: 6,000 rpm
Clutch engagement speed (+/-120): 3,400 rpm
Electrode gap: 0.02 in
Idling speed: 2,500 rpm
Ignition module air gap: 0.01 in
Maximum power speed: 9,600 rpm
Oil pump capacity, max: 20 ml/min
Oil pump capacity, min: 15 ml/min
Oil pump type: Automatic
Spark Plug: Champion RCJ6Y

Equipment

Recommended bar length, min: 18 in
Pitch: 3/8"
Recommended bar length, max: 28 in
Chain type: C83
Bar length: 81 cm
Bar length (inch): 32 in
Sprocket type: Rim 7
Gauge: .050"

Dimensions

Weight (excl. cutting equipment): 17.4 lbs

Sound and noise

Sound pressure level at operators ear: 102 dB(A)
Sound power level, guaranteed (LWA): 115 dB(A)
Sound power level, measured: 114 dB(A)

Vibration

Equivalent vibration level (ahv, eq) rear handle: 10.2 m/s2
Equivalent vibration level (ahv, eq) front handle: 6.5 m/s2

Lubricant

Oil tank volume: 1.06 US pint
Lubricant type (Engine): Husqvarna 2 stroke or equiv. at 50:1
null