Cottondale

Phone: +18503522151
3151 Main St
Cottondale, Florida
Email: trioakenterprise@gmail.com



2025 Husqvarna 120 Chainsaw

Type	Equipment	**Category**	Chainsaw
Stock#	HUS0028	**Location**	Cottondale
Year	2025	**Status**	Available
Condition	New	**Manufacturer**	Husqvarna
Model	120		

https://www.ttsoutdoor.com/unit/2025-husqvarna-120-chainsaw-943709

Call for Price

Description

OVERVIEW

120

For performance without the frills, trust the Husqvarna 120. This all-round gas saw features our proprietary X-TORQ engine to deliver superior performance, increased fuel efficiency and low emissions. Air Injection technology improves engine life by expelling larger dust and debris particles before they reach the air filter. And LowVib technology keeps this saw comfortable to use, no matter the task.

SPECIFICATIONS

16", 3/8 pitch, .050 ga. 38cc chainsaw FA CraftBx

SKU: 970 73 96-16

Engine

16", 3/8 pitch, .050 ga. 38cc chainsaw FA CraftBx
SKU: 970 73 96-16
Chain speed at max power: 55 fts
Cylinder displacement: 38 cm3
Output shaft power: 1.88 hp
Clutch engagement speed (+/-120): 4,000 rpm
Electrode gap: 0.022 in
Idling speed: 3,000 rpm
Ignition module air gap: 0.01 in
Maximum power speed: 9,000 rpm
Oil pump type: Automatic
Spark Plug: Husqvarna HQT-1

Equipment

Recommended bar length, min: 14 in
Pitch: 3/8" mini
Recommended bar length, max: 18 in
Chain type: S93G
Bar length: 40 cm
Bar length (inch): 16 in
Sprocket type: Rim 6
Gauge: .050"

Dimensions

Weight (excl. cutting equipment): 10.7 lbs

Sound and noise

Sound pressure level at operators ear: 95 dB(A)
Sound power level, guaranteed (LWA): 116 dB(A)
Sound power level, measured: 113 dB(A)

Vibration

Equivalent vibration level (ahv, eq) rear handle: 6.7 m/s2
Equivalent vibration level (ahv, eq) front handle: 5.3 m/s2

Lubricant

Oil tank volume: 0.32 US pint
Lubricant type (Engine): Husqvarna 2 stroke or equiv. at 50:1

Emission

Exhaust emissions (CO2 EU V): 957 g/kWh
null