Bunnell

Phone: +13863461919
4751 E Moody Blvd
Bunnell, Florida
Email: alloutdoors386@gmail.com



2026 H&H Trailers 7K 82X18 Aluminum Electric Tilt Low Profile Speed Loader Car Hauler

Type	Trailer or Truck Bed	**Category**	Car Hauler
Stock#	AOHH619361	**VIN**	5JWAE2322TN619361
Location	Bunnell	**Year**	2026
Status	Sold	**Condition**	New
Manufacturer	H&H Trailers	**Model**	H8218EXLA-070
Floor Length	216in / 18ft	**Floor Width**	79.25in / 6ft 7.25in
Floor Height	20.5in / 1ft 8.5in	**GVWR**	7000
Weight	1650	**Payload Capacity**	5350
Axle Capacity	3500		
Color	Aluminum	**Pull Type**	Bumper

Axles	2	**Construction**	Aluminum
Length	276in / 23ft	**Height**	20.5in / 1ft 8.5in
Width	82in / 6ft 10in		

https://alloutdoorstrailersales.com/unit/2026-h-h-trailers-7k-82x18-aluminum-electric-tilt-low-profile-speed-loader-car-hauler-986640

Price: $11,900.00

Description

2026 H&H Trailers 7K 82X18 Aluminum Electric Tilt Low Profile Speed Loader Car Hauler

Standard Features

Every Aluminum Speed Loader® Tilt Car Hauler Trailer comes equipped with a 12V hydraulic pump with push button control, a 4 amp on-board battery charger, removable aluminum fenders, and stylish aluminum wheels. Additional features include a durable aluminum frame, treated wood decking, a sealed wiring harness, LED lighting, stake pockets, and rub rails.
GVWR (lbs) 7000 lbs
GAWR (lbs/axle) 3500 lbs/axle
Curb Weight 1650 lbs
Payload 5350 lbs
Width 82"
Length 18'
Overall Length 276"
Deck Width 79.25"
Deck Height 20.5"
Height Overall 32"
Height Deck 20.5"
Width Interior 79.25"
Width Between Fender 79.25"
Width Tilting Deck 79.25
Load Angle 11
Type OPEN
Axle (2) 3500 lb. Drop Spring Brake
Bulkhead Aluminum Tube
Connector Plug Round 7-pin Blade
Coupler 2-5/16" A-Frame, Posi-Lock
Crossmembers 3" Aluminum Channel
Decking 2" Pressure Treated Pine
Dovetail Reverse Taper Cut
Exterior Lights Full LED, DOT Compliant

Exterior Storage Tongue Mounted Lockable Battery and Pump Box
Fenders Teardrop Smooth Aluminum (Both Removable)
Frame 6" Aluminum Channel
Hubs Easy Lube
Hydraulic Components 12 Volt Hydraulic Pump
Safety Chains DOT Compliant
Tie Downs Aluminum Rub Rails, Aluminum Stake Pockets
Tires ST205/75R15C 6-PLY
Tongue 6" Aluminum Channel, Fully Wrapped, Low Profile
Tongue Jack 7K Drop Leg, Set-Back
Warranty Limited 3-Year Warranty
Wheels 15", 5-Lug Aluminum
Wiring Sealed Wiring Harness

Upgrade Options this Trailer

Aluminum Extruded Decking
4 Recessed D-Rings
ATP Rockguard Fairing
Winch Mount
Spare Mount (Under Deck)

Specifications

GVWR (lbs) 7000 lbs
GAWR (lbs/axle) 3500 lbs/axle
Curb Weight 1650 lbs
Payload 5350 lbs
Width 82"
Length 18'
Overall Length 276"
Deck Width 79.25"
Deck Height 20.5"
Height Overall 32"
Height Deck 20.5"
Width Interior 79.25"
Width Between Fender 79.25"
Width Tilting Deck 79.25
Load Angle 11
Type OPEN
Axle (2) 3500 lb. Drop Spring Brake
Bulkhead Aluminum Tube
Connector Plug Round 7-pin Blade
Coupler 2-5/16" A-Frame, Posi-Lock
Crossmembers 3" Aluminum Channel
Decking 2" Pressure Treated Pine
Dovetail Reverse Taper Cut
Exterior Lights Full LED, DOT Compliant
Exterior Storage Tongue Mounted Lockable Battery and Pump Box
Fenders Teardrop Smooth Aluminum (Both Removable)

Frame 6" Aluminum Channel
Hubs Easy Lube
Hydraulic Components 12 Volt Hydraulic Pump
Safety Chains DOT Compliant
Tie Downs Aluminum Rub Rails, Aluminum Stake Pockets
Tires ST205/75R15C 6-PLY
Tongue 6" Aluminum Channel, Fully Wrapped, Low Profile
Tongue Jack 7K Drop Leg, Set-Back
Warranty Limited 3-Year Warranty
Wheels 15", 5-Lug Aluminum
Wiring Sealed Wiring Harness
